

APPARATUS AND METHOD FOR CONTROLLING A FOCUS POSITION FOR A DIGITAL STILL CAMERA

BACKGROUND OF THE INVENTION

Field of the Invention

5 The present invention relates to an apparatus and a method for controlling a focus position for a digital still camera, and more particularly, to an apparatus and method for controlling a focus position for a digital still camera, which allows a user to move a focus to a desirable position on a subject.

Description of the Prior Arts

10 A conventional digital still camera is a device which uses an electronic sensor such as a charge coupled device (CCD), to capture an image; a digital camera processor (DCP) to convert analog image signals from the CCD into digital image signals; a storage device to store the digital image signals; and a liquid crystal display
15 (LCD) to display the digital image signals.

 Conventionally, an autofocus system of a digital camera utilizing image signals of DCP in focusing marks a focus position on an LCD. The mark is fixed at the center of the LCD and a user should locate a subject to be focused at the center of the LCD and take a photograph.

20 Therefore, even when the subject to be focused is not located at the center of the frame, the camera assumes that the center of the frame needs to be focused and has the real subject intended to be focused be out of focus.

SUMMARY OF THE INVENTION

It is an objective of the present invention to provide an apparatus and a method for controlling a focus position for a digital still camera. It is also an object of the present invention to provide an apparatus and a method for moving a focus position to
5 a desirable position of a subject.

To achieve the objective and in accordance with the purpose of the invention, as embodied and broadly described herein, the invention comprises a display unit for displaying an image corresponding to a subject and a mark representing a focus position, a switch unit for moving the mark on the display unit according to a user's
10 request. The invention further comprises a focus controller for controlling focus on the mark displayed on the display unit.

Also, to achieve this objective, the present invention comprises the steps of determining whether a user inputs a movement of the focus position, displaying the inputted focus position when the user inputs a movement of the focus position, focusing
15 on the position of a subject corresponding to the displayed focus position.

BRIEF DESCRIPTION OF THE DRAWINGS

The accompanying drawings, which are incorporated in and constitute a part of this specification, illustrate one embodiment of the invention and, together with the description, serve to explain the principles of the invention. In the drawings:

20 FIG. 1 is a block diagram of a digital still camera in accordance with a preferred embodiment of the present invention;

FIG. 2 is a flowchart showing the operation for controlling a focus position for a digital still camera in accordance with a preferred embodiment of the present invention;

FIG. 3 is a diagram showing the movement of the mark displayed on the LCD;

FIG. 4 is a flowchart showing the operation of the focusing process subroutine

5 called in the main routine of FIG. 2.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

Reference will now be made in detail to the preferred embodiment of the present invention, an example of which is illustrated in the accompanying drawings.

As shown in FIG. 1, a digital still camera comprises a lens/lens driving unit 10
 10 generating an image by collecting light from the subject, a photoelectric converting unit
 20 for generating electric signals corresponding to the image generated by the lens/lens
 driving unit 10, a switch unit 30 established on the camera body for moving a focus
 position and for starting photographing according to a user's selection, an LCD unit 40
 for displaying the image. The switch unit 30 comprises arrow keys or a joy stick. The
 15 LCD unit 40 comprises a LCD screen 42 for displaying the image and a touch screen
 44 for moving the focus position according to the user's selection. The active area of
 the LCD screen 42 is covered by the touch screen 44. The apparatus further
 comprises a frame memory unit 50 for storing image data, and a flash memory card unit
 60 for storing a compressed image data, an image signal processing unit 70 for
 20 generating image data by processing the electric signals generated from the
 photoelectric converting unit 20, for storing the image data in the frame memory unit 50,

354007-662960

and for displaying the image data on the LCD screen 42. The apparatus additionally comprises a focus control unit 80 that moves a focus position according to the user's selection through the switch unit 30 or the touch screen 44 and displays the relocated focus position on the LCD unit 40 by controlling the image signal processing unit 70.

5 The focus control unit 80 generates a value of the focus position by processing the image data stored in the frame memory unit 50 corresponding to the relocated focus position and focuses the new subject by controlling the lens/lens driving unit 10 according to the value of the focus position. The focus control unit 80 also compresses the image data stored in the frame memory unit 50 when the user selects to photograph
10 via the switch unit 30, and stores the compressed image data in the flash memory card unit 60 by the image signal processing unit 70. Further, the focus control unit 80 restores the compressed image data in the flash memory card unit 60 and stores the frame memory unit 50 as needed. The digital still camera comprises a release switch(not shown) for taking a photograph. The release switch operates at two phases.
15 The camera executes the operation of a focusing process at the first phase of the release switch. If further pressed, the camera executes the operation of storing an image of the subject at the second phase of the release switch.

As shown in FIG. 3, a mark 100 represents the focus position of the LCD unit 40. The mark 100 is located at the center of the LCD unit 40 early when the camera
20 turns on. Then, an initial focus position is on the center of the image displayed on the LCD unit 40. If a user moves the mark 100 using the switch unit 30 or the touch screen 44, the user can move the focus position anywhere on the image displayed on the LCD

unit 40.

Now, referring to FIGs. 1, 2, 3 and 4, the operation of the apparatus for controlling a focus position for a digital still camera in accordance with a preferred embodiment of the present invention will be explained.

5 At step S1, a user faces the lens/lens driving unit 10 of the digital still camera to a subject after the camera is turned on. Then, the lens/lens driving unit 10 forms an image of the subject. The photoelectric converting unit 20 generates electric signals corresponding to the image formed by the lens/lens driving unit 10 and transmits the signals to the image signal processing unit 70, which generates image data
10 corresponding to the signals. Then, the image signal processing unit 70 stores the image data in the frame memory unit 50 and transmits the image data to the LCD unit 40 to displays the image.

Next, at step S2, the user views a picture in the LCD unit 40. The mark 100 is on a car located at the center of the LCD unit 40 and initially the car located at the
15 center of the LCD unit 40 is focused. A user can move the focus position by using the switch unit 30 that has arrow keys or a joy stick or the touch screen 44 without changing the frame and composition of the picture. The user may relocate the mark 100 through the switch unit 30 or the touch screen 44 to a non-center position of the LCD unit 40, for example, to a person of Fig. 3. Accordingly, the final picture will be focused on the
20 person.

If the user relocates the mark 100 through the switch unit 30 or the touch screen 44, the focus control unit 80 controls the image signal processing unit 70 in

order to display the relocated mark 100 on the LCD unit 40, at step S3. Next, at step S4, the focus control unit 80 checks the state of release switch. If the release switch is at the first phase, then the operation goes to step S5, where the image signal processing unit 70 stores the image data of the subject in the frame memory unit 50 and transmits the image data to the LCD unit 40 to displays the image. Next, at step S6, the focus control unit 80 calculates an address of the frame memory unit 50 corresponding to coordinates of the mark 100 displayed on the LCD unit 40. Image data corresponding to the position of the mark 100 are stored in the calculated address of the frame memory unit 50. At step S7, the focus control unit 80 controls the image signal processing unit 70 to read the image data stored in the calculated address of the frame memory unit 50. Next, the image signal processing unit 70 processes the image data in order to focus the lens 10. Then, the focus control unit 80 generates a focus value using the processed image data, at step S8

At step S9, the focusing process subroutine is executed. Referring to FIG. 4, the operation of the focusing process subroutine at step S9 will be explained.

At step S71, the image signal processing unit has the focus control unit 80 advance the lens 10 by one focusing step. At step S72, the focus control unit 80 generates a present focus value. Next, at step S73, the focus control unit 80 determines whether the present focus value is larger than the prior focus value generated at step S8. If the present focus value is larger than the prior focus value, then steps S71 and S72 are repeated. However, if the present focus value is not larger than the prior focus value, then the operation proceeds to step S74.

At step S74, the focus control unit 80 determines whether the present focus value is smaller than the prior focus value. If the present focus value is smaller than the prior focus value, then the operation goes to step S75, where the focus control unit 80 backs the lens 10 by one focusing step. Next, step S72 and S73 are repeated.

5 However, if the present focus value is not smaller than the prior focus value, that is, if a maximum focus value is found, then the operation proceeds to step S76.

At step S76, the focus control unit 80 fixes the lens 10. Next, the focus control unit 80 turns on an autofocus LED(light emitting diode) which signifies a completion of the focusing process.

10 Consequently, at step S9, the focus control unit 80 focuses on the person by controlling the lens/lens driving unit 10 according to the calculation for focus adjustment. Accordingly, the person is focused corresponding to the mark 100 as displayed on the LCD unit 40.

Next, the focus control unit 80 determines whether the state of the release switch is at the second phase, at step S10. If the state of the release switch is at the second phase, then the picture is taken, at step S11. The picture is taken as follows. The focus control unit 80 compresses the image data stored in the frame memory unit 50. Next, the image signal processing unit 70 stores the compressed data in the flash memory card unit 60. Consequently, the data stored in the flash memory card unit 60 is
20 photographic image data of the subject.

As described above, since a user can relocate a focus point to a desirable position of a subject, a user can take a picture having a certain position focused without

changing the frame or composition of the picture.

Other embodiments of the invention will be apparent to those skilled in the art from consideration of the specification and practice of the invention disclosed herein. It is intended that the specification and examples be considered as exemplary only, with a true scope and spirit of the invention being indicated by the following claims.

5

362007-6E529T60